

Riemannian Multinomial Logistics Regression for SPD Neural Networks

– CVPR 2024 –

Ziheng Chen¹, Yue Song¹, Gaowen Liu², Ramana Rao Kompella², Xiaojun Wu³, Nicu Sebe¹

1 University of Trento, Italy 2 Cisco Systems, USA 3 Jiangnan University, China










Applications of SPD Manifolds




2



Huang, Zhiwu, Jiqing Wu, and Luc Van Gool. "Manifold-valued image generation with wasserstein generative adversarial nets." AAAI, 2019. Chakraborty, Rudrasis, et al. "Manifoldnet: A deep neural network for manifold-valued data with applications." IEEE-TPAMI, 2020. Ju, Ce, et al. "Deep geodesic canonical correlation analysis for covariance-based neuroimaging data." ICLR, 2024. Nguyen, Xuan Son. "Geomnet: A neural network based on riemannian geometries of SPD matrix space and cholesky space for 3D skeleton-based interaction recognition." ICCV, 2021. Brooks, Daniel, et al. "Deep learning and information geometry for drone micro-Doppler radar classification." RadarConf, 2020.

Classification on SPD Neural Networks





Chakraborty, Rudrasis, et al. "A statistical recurrent model on the manifold of symmetric positive definite matrices." Neurips, 2018.



SPDMLR:

- A general framework for SPD Multinomial Logistics Regression (MLR) under PEMs
- Specific SPD MLRs under parameterized LCM and LEM
- An intrinsic theoretical explanation of the most popular LogEig classifier

MLR Revisiting



 $\forall k \in \{1, \dots, C\}, p(y = k \mid x) \propto \exp\left(\left(\langle a_k, x \rangle - b_k\right)\right)$ Reformulation into margin distance
to hyperplane $p(y = k \mid x) \propto \exp(\operatorname{sign}(\langle a_k, x - p_k \rangle) ||a_k|| d(x, H_{a_k, p_k}))$ $H_{a_k, p_k} = \{x \in \mathbb{R}^n : \langle a_k, x - p_k \rangle = 0\}$

Gyro SPD MLR:

Euclidean MLR:

- Requires gyro vector structures
- Relies on gyro distance, instead of geodesic distance
- Solves formulation case by case

Our SPD MLR:

- Focus on Pullback Euclideam Metrics (PEMs)
- Only needs Riemannian geometry
- Relies on geodesic distance
- Proposes a general formulation for PEMs

SPD MLR under PEMs



From Euclidean to SPD

 $p(y = k \mid x) \propto \exp(\operatorname{sign}(\langle a_k, x - p_k \rangle) \| a_k \| d(x, H_{a_k, p_k})) \qquad H_{a_k, p_k} = \{x \in \mathbb{R}^n : \langle a_k, x - p_k \rangle = 0\}$ Riemannian reformulation

Definition 3.1 (SPD hyperplanes). Given $P \in S_{++}^n$, $A \in T_P S_{++}^n \setminus \{0\}$, we define the SPD hyperplane as

$$\tilde{H}_{A,P} = \{ S \in \mathcal{S}_{++}^n : g_P(\operatorname{Log}_P S, A) = \langle \operatorname{Log}_P S, A \rangle_P = 0 \},$$
(12)

where P and A are referred to as shift and normal matrices, respectively.

Definition 3.2 (SPD MLR). SPD MLR is defined as

$$p(y = k \mid S) \propto \exp(\operatorname{sign}(\langle A_k, \operatorname{Log}_{P_k}(S) \rangle_{P_k}) \|A_k\|_{P_k} d(S, \tilde{H}_{A_k, P_k})),$$
(13)

where $P_k \in S_{++}^n$, $A_k \in T_{P_k}S_{++}^n \setminus \{0\}$, $\langle \cdot, \cdot \rangle_{P_k} = g_{P_k}$, and $\|\cdot\|_{P_k}$ is the norm on $T_{P_k}S_{++}^n$ induced by g at P_k , and \tilde{H}_{A_k,P_k} is a margin hyperplane in S_{++}^n as defined in Eq. (12). $d(S, \tilde{H}_{A_k,P_k})$ denotes the margin distance between S and SPD hyperplane \tilde{H}_{A_k,P_k} , which is formulated as:

$$l(S, \tilde{H}_{A_k, P_k})) = \inf_{Q \in \tilde{H}_{A_k, P_k}} d(S, Q), \tag{14}$$

where d(S, Q) is the geodesic distance induced by g.

Proposition 3.3 (Submanifolds). *The SPD hyperplane (as defined in Eq.* (12)) *under any geometrically complete Riemannian metric g is a regular submanifold of SPD manifolds.*

Submanifolds are natural generalizations of the Euclidean hyperplanes.

SPD MLR under PEMs



Margin distance and MLR

Margin distance:

$$d(S, \tilde{H}_{A_k, P_k})) = d(\phi(S), H_{\phi_{*, P_k}(A_k), \phi(P_k)}),$$
(15)

$$=\frac{|\langle\phi(S) - \phi(P_k), \phi_{*, P_k}(A_k)\rangle|}{\|A_k\|_{P_k}},$$
(16)

where $|\cdot|$ is the absolute value.

under a PEM.

Optmization:

General formulation:

Lemma 3.6. Given a PEM, any parallel transportation is equivalent to the differential map of a left translation and vice versa. **Lemma 3.7.** Given two fixed SPD matrices $Q_1, Q_2 \in S_{++}^n$, we have the following equivalence for parallel transportations

$$\forall \tilde{A}_{1,k} \in T_{Q_1} \mathcal{S}^n_{++}, \exists ! \tilde{A}_{2,k} \in T_{Q_2} \mathcal{S}^n_{++},$$

$$s.t. \Gamma_{Q_1 \to P_k}(\tilde{A}_{1,k}) = \Gamma_{Q_2 \to P_k}(\tilde{A}_{2,k}).$$

$$(18)$$

Theorem 3.8 (SPD MLR under a PEM). Under any PEM, SPD MLR and SPD hyperplane is

$$\phi(y = k \mid S) \propto \exp(\langle \phi(S) - \phi(P_k), \phi_{*,I}(\tilde{A}_k) \rangle), \tag{19}$$

$$\tilde{H}_{\tilde{A}_{k},P_{k}} = \{ S \in \mathcal{S}_{++}^{n} : \langle \phi(S) - \phi(P_{k}), \phi_{*,I}(\tilde{A}_{k}) \rangle = 0 \},$$
(20)

where $\tilde{A}_k \in T_I \mathcal{S}_{++}^n / \{0\} \cong \mathcal{S}^n / \{0\}$ is a symmetric matrix, and $P_k \in \mathcal{S}_{++}^n$ is an SPD matrix.

MLR on the parameterized LEM and LCM




Corollary 4.1 (SPD MLRs under the deformed LEM and LCM). *The SPD MLRs under* (α, β) -*LEM is*

$$p(y = k \mid S) \propto \exp\left[\langle \operatorname{mlog}(S) - \operatorname{mlog}(P_k), \tilde{A}_k \rangle^{(\alpha, \beta)}\right],$$
(21)

where $\tilde{A}_k \in T_I \mathcal{S}_{++}^n \cong \mathcal{S}^n$ and $P_k \in \mathcal{S}_{++}^n$. The SPD MLRs under (θ) -LCM is

 $p(y = k \mid S) \propto \exp\left[\frac{1}{\theta} \langle \lfloor \tilde{K} \rfloor - \lfloor \tilde{L}_k \rfloor + \left[\operatorname{Dlog}(\mathbb{D}(\tilde{K})) - \operatorname{Dlog}(\mathbb{D}(\tilde{L}_k)) \right], \lfloor \tilde{A}_k \rfloor + \frac{1}{2} \mathbb{D}(\tilde{A}_k) \rangle \right],$ (22)

where $\tilde{K} = \text{Chol}(S^{\theta})$, $\tilde{L}_k = \text{Chol}(P_k^{\theta})$, and $\mathbb{D}(\tilde{A}_k)$ denotes a diagonal matrix with diagonal elements of \tilde{A}_k .



Visualization of SPD hyperplane

Figure 1. Conceptual illustration of SPD hyperplanes induced by (α, β) -LEM and (θ) -LCM. In each subfigure, the black dots are symmetric positive semi-definite (SPSD) matrices, denoting the boundary of S^2_{++} , while the blue, red, and yellow dots denote three SPD hyperplanes.

Experiments



Backbone	Classifier	[20,16,8]	[20,16,14,12,10,8]
SPDNet	LogEig MLR Gyro-AIM	92.88±1.05 94.53±0.95	93.47±0.45 94.32±0.94
	(1,0)-LEM (1,1)-LEM	93.55±1.21 95.64±0.83	94.60±0.70 95.87±0.58
	(1)-LCM (0.5)-LCM	93.49±1.25 94.59±0.82	93.93±0.98 95.16±0.67

Backbone	Classifier	[93,30]	[93,70,30]	[93,70,50,30]
	LogEig MLR	57.42±1.31	60.69±0.66	60.76±0.80
	Gyro-AIM	58.07±0.64	60.72±0.62	61.14±0.94
SPDNet	(1,0)-LEM	57.02±0.75	61.34±0.62	60.78±0.86
	(1)-LCM	62.04±1.05	62.11±2.11	62.89±2.09
	(0.5)-LCM	65.66±0.73	65.79±0.63	65.71±0.75

Table 3. Results of SPDNet with different classifiers on the Radar dataset.

Backbone	Classifier	Inter-session	Inter-subject
SPDDSMBN	LogEig MLR Gyro-AIM	53.83±9.77 53.36±9.92	49.68±7.88 50.65±8.13
	(1,0)-LEM	53.16±9.73	51.41±7.98
	(1)-LCM (1.5)-LCM	55.71±8.57 56.43±8.79	51.60±8.43 51.65±5.90

Table 5. Results of SPDDSMBN with different classifiers on the Hinss2021 dataset under inter-subject and inter-session scenarios. The presented results are the ones of balanced accuracy under the leaving 5% out cross-validation scenario.

Table 4. Results of SPDNet with different classifiers on theHDM05 dataset.

			Hinss2021	
Methods	Radar	HDM05	inter-session	inter-subject
Baseline	1.36	1.95	0.18	8.31
MLR-Gyro-AIM	1.75	31.64	0.38	13.3
MLR-LEM	1.5	4.7	0.24	10.13
MLR-LCM	1.35	3.29	0.18	8.35

Table 6. Comparison of training efficiency (s/epoch) of SPDNet (SPDDSMBN) under different classifiers. The most efficient MLR is highlighted in **bold**.

Huang, Zhiwu, and Luc Van Gool. "A riemannian network for spd matrix learning." AAAI, 2017.

Kobler, Reinmar, et al. "SPD domain-specific batch normalization to crack interpretable unsupervised domain adaptation in EEG." Neurips, 2022.





Thanks you Q & A



Code



Paper



Homepage